

## **Biogas Plant NOYON**



Location Period: 2008/09  Input substrat: Sludge, fat, process water, cofermente, food residues  Fermenter: Steel tank 3,500 m³  CHP Gas engine 716 kW  Special Features: Gas holder above secondary digester tank, mesophilic operation, separation of digestates, recirculation of process water, compost works, external heat use  Cost: Approximately EUR 6,4 Mio (incl. composting facility)		
Input substrat:  Sludge, fat, process water, cofermente, food residues  Fermenter:  Steel tank 3,500 m³  CHP  Gas engine 716 kW  Special Features:  Gas holder above secondary digester tank, mesophilic operation, separation of digestates, recirculation of process water, compost works, external heat use  Cost:  Approximately EUR 6,4 Mio (incl. composting	Location	Picardie, France
residues  Fermenter: Steel tank 3,500 m³  CHP Gas engine 716 kW  Special Features: Gas holder above secondary digester tank, mesophilic operation, separation of digestates, recirculation of process water, compost works, external heat use  Cost: Approximately EUR 6,4 Mio (incl. composting	Construction Period:	2008/09
CHP Gas engine 716 kW  Special Features: Gas holder above secondary digester tank, mesophilic operation, separation of digestates, recirculation of process water, compost works, external heat use  Cost: Approximately EUR 6,4 Mio (incl. composting	Input substrat:	
Special Features:  Gas holder above secondary digester tank, mesophilic operation, separation of digestates, recirculation of process water, compost works, external heat use  Cost:  Approximately EUR 6,4 Mio (incl. composting	Fermenter:	Steel tank 3,500 m³
mesophilic operation, separation of digestates, recirculation of process water, compost works, external heat use  Cost: Approximately EUR 6,4 Mio (incl. composting	CHP	Gas engine 716 kW
	Special Features:	mesophilic operation, separation of digestates, recirculation of process water, compost works,
	Cost:	, , ,

The biogas plant NOYON in France, built and operated by Ferti-NRJ SA is a waste digestion plant with mesophilic operation. This is followed by dewatering and composting of the digestate. The facility is designed to process sludge, fat, municipal organic waste, co-fermentation residues and process water. The biogas plant layout consists of one reception tank for the process water, one mixing tank, a reception tank for fat, one upright primary fermenter with a topmounted agitator and a secondary digestion tank with a gasholder roof. The composting facility is located at the site. The fat is separately led into the fermenter through the use of an eccentric screw pump. The engineering of the biogas system is configured as a single-stage system and offers a phase separation of the digestate into solid and liquid phases. The separated liquid phase is used for the dilution of the input substrates while the solid phase is dried and then composted. The biogas produced is recovered by a gas engine with a capacity of 716 kWel. The electricity is supplied to the public grid connection. The generated heat is used for the drying of the digestate. Start-up of the biogas plant was in 2009

Krieg & Fischer Ingenieure GmbH
Maschmühlenweg 10
D-37073 Göttingen – Germany
Tel,: +49 551 90 03 62 – 0
Fax,: +49 551 90 03 63 – 29
contact@KriegFischer.de
www.KriegFischer.de

Responsibility of Krieg & Fischer Ingenieure GmbH: Conception, Preplanning, Permission, Detailed and Final Construction, Supervision and Start-up