



Sustainable Management of Waste by anaerobic Digestion

Torsten Fischer

Krieg & Fischer Ingenieure GmbH
Hannah-Vogt-Strasse 1, D-37085 Göttingen, Allemande
phone: +49 551 3057432, fax: +49 551 7707712
Fischer@KriegFischer.de
www.KriegFischer.de

Americana 2007, Montreal, March, 20th, 2007



Krieg & Fischer Ingenieure GmbH

Engineering Office, Planning and Construction

Founded: 1999

Experience: 20 Years


References: about 120 total

about 90 farm-scale


Germany, Japan, Netherlands, Austria,
Switzerland, Lithuania, Italy, Slovakia, Canada,
USA, Spain, France

Team: 14


Partners: Japan, USA, Austria, Bulgaria, France,
Hungary, Turkey, Poland, Ireland



KF



Biogas Plants in Germany





Fachverband
Biogas e.V.

German Biogas Association • Asociación Alemana de Biogás • Société Allemande du Biogaz



KF







Planning of Biogas Plants


- ⇒ Type of Input Substrate
- ⇒ Amount of Input Substrate per Year
- ⇒ Local Circumstances
- ⇒ Heat Usage
- ⇒ Pasteurisation
- ⇒ Automation Level



Im Brahm



Im Brahm







Im Brahm


pig manure,
kitchen waste






Standard Digester in Agriculture


(up to 1.250 m³ Volume)





KF





90,000 m³ manure

20,000 m³ fats


WERLTE






Upright Large Digester

(up to 5.000 m³ Volume)









	Biogas plant IM BRAHM	Biogas plant WERLTE
Location	Essen, Germany 150 m distance to a residential area and adjacent to a water protection area (WSG II)	Werlte, Germany in a water protection area (WSG III)
Construction period	2005	2002/2003
Planned input	6,250 t/a	110,000 t/a
Input material	manure (2,555 t/a) horse dung (2,750 t/a) kitchen waste, fats (8,395 t/a) total: 13,700 t/a	manure (41,000 t/a) cosubstrates (33,000 t/a) as: fats, kitchen waste, gastrointestinal-tracts and content and blood total: 74,000 t/a
Co-Generator	gas engine (2 x 190 kW) containerized	gas engine (2 x 1,262 kW) containerized
Heat usage	Pasteurisation, farm buildings	Pasteurisation



	Biogas plant IM BRAHM	Biogas plant WERLTE
Temperature	mesophilic	mesophilic
Digester heating mixing operation	1 concrete tank (1,205 m ³) internal pipe heating system side mounted agitator unit (2 x 11 kW) 2-stage digestion	2 steel tanks (2 x 3,200 m ³) external heat exchanger top-mounted mixer (2 x 11 kW) 1-stage digestion
Investment	Euro 1 Million	Euro 6 Million
delivery	reception hall with biofilter	reception hall with biofilter
pretreatment	grinding and full stream pasteurisation (70° C, 1 h)	grinding and full stream pasteurisation (70° C, 1 h)
Solid input device	for horse dung	-
receipts	50 Euro/t (average)	5 Euro/t
Necessary expert's reports	odor emissions noise	odor emissions noise



Economical Background in Germany

- Income until 2000: about 50% by tipping fee for waste, about 50% by selling electricity to public grid
- Income until 2004: about 25% by tipping fee for waste, about 75% by selling electricity to public grid
- Income now: 100% by selling electricity to public grid (energy crops and manure); about 25% by tipping fee for waste, about 75% by selling electricity to public grid (waste digestion)

→ all the time: low interest rates for investment in renewable energies



Planning of Biogas Plants

- ⇒ Type of Input Substrate
- ⇒ Amount of Input Substrate per Year
- ⇒ Local Circumstances
- ⇒ Heat Usage
- ⇒ Pasteurisation
- ⇒ Automation Level



Sustainable Management of Waste by anaerobic Digestion

Torsten Fischer

Krieg & Fischer Ingenieure GmbH
Hannah-Vogt-Strasse 1, D-37085 Göttingen, Allemande
phone: +49 551 3057432, fax: +49 551 7707712
Fischer@KriegFischer.de
www.KriegFischer.de

Americana 2007, Montreal, March, 20th, 2007